

800 SERIES

Bottle Filling Machine



- Simple, fast, and 100% accurate
- Precise fill control
- Advanced chip detection



800 SERIES

FEATURES

- High speeds of over 400 BPM
- 100% accurate counts
- Tool-less changeovers
- Advanced chip detection
- Multiple recipe setups
- Wheel sequence mode for small production runs – on the fly
- Easily cleaned for pharmaceutical guidelines (cGMP)
- Digital servo drives for greater precision
- CFR21 part 11 compliant
- Minimal change parts
- User friendly touch screen interface
- Network ready
- Two year warranty

TECHNICAL SPECIFICATIONS

- Single Lane** Max. Bottle: 180mm HT X 110 Dia.
Min. Bottle: 25mm HT X 34.5mm Dia.
- Dual Lane** Max. Bottle: 180mm HT x 55mm Dia.
Min. Bottle: 25mm HT x 32.5mm Dia.

AVAILABLE MODELS

ACT810SL & DL
ACT815DL
ACT820DL

UTILITIES

- Power Supply** 208V, 3-phase,
50/60Hz
- Connecting Load** 16AMPs
- Compressed Air** 80psi



Innovative design and manufacture of solid-dose packaging automation.

Aylward Enterprises, LLC. | 401 Industrial Drive | New Bern, North Carolina 28562

P (252) 633-5757 | F (252) 637-6671 | E info@aylward-usa.com | aylward-usa.com

Product Name	Product Dimensions (mm) Dia. x Thk.	Product Count	Bottles per Minute			
			ACT810SL	ACT810DL	ACT815DL	ACT820DL
20 mg, round, convex, uncoated tablet	7.1 X 2.8	30	155-165	230-240	325-335	300-310
		60	100-110	130-140	190-200	255-265
		100	80-90	100-110	145-155	195-205
		1000	5 - 7	5 - 7	5-10	10-15
#1 capsule	6.91 x 19.4	30	150-160	210-220	310-320	300-310
		60	95-105	125-135	180-190	235-245
		100	75-85	90-100	135-145	180-190
		1000	1-3	1-3	5-7	7-12
Caplet, Convex	5.75 x 3.45 x 11.47	30	140-150	195-205	280-290	300-310
		60	85-95	105-115	155-165	205-215
		100	65-75	75-85	115-125	155-165
		1000	1-3	1-3	2-4	7-9

