

9000 SERIES

Bottle Filling Machine



- Simple, fast, and 100% accurate
- Precise fill control
- Built-in product containment



9000 SERIES

FEATURES

- High speeds of over 400 BPM
- 100% accurate count
- Product containment is standard
- Tool-less changeovers
- Advanced chip detection
- Tablet inspection
- Easy recipe setups
- Bottle Sampling
- Easily cleaned for pharmaceutical guidelines (cGMP)
- Highly customized HMI interface and graphics
- Digital servo drives for greater precision
- CFR21 part 11 compliant
- Minimal change parts
- Small footprint
- User friendly touch screen interface
- Network ready
- Two year warranty
- Available for low, medium, and high output

TECHNICAL SPECIFICATIONS

Single Lane Max. Bottle: 205mm HT X 130mm Dia.
Min. Bottle: 20mm HT X 25mm Dia

Dual Lane Max. Bottle: 205mm HT x 70mm Dia.
Min. Bottle: 20mm HT x 25mm Dia.

AVAILABLE MODELS

ACT 9200 SL & DL (12 fill stations)
ACT 9300 DL (18 fill stations)
ACT 9400 DL (24 fill stations)

UTILITIES

Power Supply 208V, 3-phase, 50/60Hz

Connecting Load 16AMPs

Compressed Air 80psi



Innovative design and manufacture of solid-dose packaging automation.

Aylward Enterprises, LLC. | 401 Industrial Drive | New Bern, North Carolina 28562

P (252) 633-5757 | F (252) 637-6671 | E info@aylward-usa.com | aylward-usa.com

Product Name	Product Dimensions (mm) Dia. x Thk.	Product Count	Bottles per Minute			
			9200SL	9200DL	9300DL	9400DL
20 mg, round, convex, uncoated tablet	7.1 X 2.8	30	175-185	200-210	260-270	300-310
		60	145-155	200-210	260-270	300-310
		100	115-125	200-210	260-270	300-310
		1000	10-20	20-25	25-30	40-45
#1 Capsule	6.91 x 19.4	30	165-175	200-210	260-270	300-310
		60	140-150	200-210	260-270	300-310
		100	105-115	175-185	260-270	300-310
		1000	15-20	15-20	25-30	30-35
Caplet, Convex	5.75 x 3.45 x 11.47	30	155-165	200-210	260-270	300-310
		60	175-185	200-210	260-270	300-310
		100	95-105	150-160	230-240	300-310
		1000	10-15	10-15	20-25	25-30

